

TAB - Standard Output Character Translation

This Natural profile parameter is for mainframes only.

It allows you to overwrite the definitions in the translation table NTTAB as contained in the configuration module NATCONFIG. The NTTAB table is the standard output translation table.

TAB corresponds to the NTTAB macro in the Natural parameter module NATPARM.

Possible settings	See TAB Parameter Syntax below.	
Default setting	As specified within the macro NTTAB in NATCONFIG.	
Dynamic specification	YES	This parameter can only be specified dynamically. In the Natural parameter module NATPARM, the macro NTTAB must be used instead.
Specification within session	NO	

The following topics are covered below:

- TAB Parameter Syntax
- NTTAB Macro Syntax
- Example of NTTAB Macro
- Example of TAB Parameter

TAB Parameter Syntax

The TAB parameter is specified as follows:

```
TAB=( a1,a2,b1,b2,c1,c2,... )
```

You specify pairs of characters, the first character of a pair being the character to be translated, the second character of a pair being the character into which the first character is to be translated.

You can specify each character either as the one-byte character itself (enclosed in apostrophes) or as the hexadecimal representation of that character.

NTTAB Syntax

The NTTAB macro is specified as follows:

```
NTTAB a1,a2,b1,b2,c1,c2,...
```

Example of NTTAB Macro

```
NTTAB 5E,'Ä','ö',78,FF,00,'ü','Ü'
```

In this example, the character represented by H'5E' is translated into "Ä", "ö" into the character represented by H'78', the character represented by H'FF' into the character represented by H'00', and "ü" into "Ü".

Example of TAB Parameter

With the TAB parameter, you must enclose the entire string of character pairs in parentheses, for example:

```
TAB=(5E,'Ä','ö',78,FF,00,'ü','Ü')
```